

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



(43) International publication date

3 March 2005 (03.03.2005)

(10) International publication number

WO 2005/020376 A1

PCT

(51) International patent classification⁷:
4/24

H01R 12/04,

(74) Joint Representative: KRONE GMBH; Abteilung
HRP, Beeskowdamm 3-11, 14167 Berlin (DE).

(21) International application number: PCT/EP2004/006821

(22) International filing date: 24 June 2004 (24.06.2004)

(25) Language of filing: German

(26) Language of publication: German

(30) Data relating to the priority:
103 33 913.2 25 July 2003 (25.07.2003) DE

(71) Applicant (for all designated States except US): KRONE
GMBH [DE/DE]; Beeskowdamm 3-11, 14167 Berlin (DE).

(72) Inventor; and

(75) Inventor/Applicant (US only): NEUMETZLER, Heiko
[DE/DE]; Breite Strasse 23, 12167 Berlin (DE).

(81) Designated states (unless otherwise indicated, for
every kind of national protection available): AE, AG,
AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY,
BZ, CA, CH, CN, CO, CR, CU, CZ, DK, DM, DZ, EC,
EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID,
IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS,
LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ,
NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ,
UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated states (unless otherwise indicated, for
every kind of regional protection available): ARIPO
patent (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL,
SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY,
KG, KZ, MD, RU, TJ, TM), European patent (AT, BE,
BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR,

[continued on next page]

As printed

(54) Title: CONDUCTOR CONNECTING MODULE FOR PRINTED CIRCUIT BOARDS

(54) Bezeichnung: ADERANSCHLUSSMODUL FÜR LEITERPLATTEN



(57) Abstract: The invention relates to a conductor connecting module (1) for printed circuit boards, comprising a housing (2) in which contact elements are disposed. Said contact elements have a first contact area that is configured as an insulation displacement contact (3), and a second contact area that is configured as a solderable contact pin (4). The contact pins (4) are disposed at a right angle to the insulation displacement contacts (3) so that the insulation displacement contacts (3), in the mounted state, lie in a plane parallel to the printed circuit board (6).

(57) Zusammenfassung: Die Erfindung betrifft ein Aderanschlussmodul (1) für Leiterplatten, umfassend ein Gehäuse (2), in dem Kontaktelemente angeordnet sind wobei die Kontaktelemente einen ersten Kontaktbereich aufweisen, der als Schneid-Klemm-Kontakt (3) ausgebildet ist, und einen zweiten Kontaktbereich aufweisen, der als lötlarer Kontaktpin (4) ausgebildet ist, wobei die Kontaktpins (4) in einem rechten Winkel zu den Schneid-Klemm-Kontakten (3) angeordnet sind, so dass die Schneid-Klemm-Kontakte (3) im montierten Zustand in einer Ebene parallel zur Leiterplatte (6) liegen.

WO 2005/020376 A1

WO 2005/020376

HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For an explanation of the two-letter codes and the other abbreviations, reference is made to the explanations ("Guidance Notes on Codes and Abbreviations") at the beginning of each regular edition of the PCT Gazette.

Published:

- *With International Search Report.*